# **FUTUREWAY® FA141**

**Unsintered PTFE Tape** 

FA141 series are standard and unsintered tapes for high-temperature, chemical resistant, and light weight wires for aviation and aerospace industry. FA141 has more bight color proptery.

#### Features and Benefits:

- High-temperature operation
- Custom color
- Fire resistance
- High dielectric strength
- SAE AS22759 requirement
- RoHS compliant



### SHENZHEN FUTUREWAY TECHNOLOGY CO., LTD

Dedicated to be a material expert for customers



## FUTUREWAY® FA141 is ideal for:

- · Aircraft installation wire insulation
- Aircraft installation wire jacket

PROPERTY	TEST METHOD	VALUE
Density (g/cc)		1.50 ± 0.05
Color		Natural/custom
Thickness (mm/mil)	GB/T 6672-2001	0.051 - 0.127/ 2 - 5
Thickness		± 0.005
tolerance (mm)		± U.UU⊃
Width (mm)	GB/T 6672-2001	2 - 100
Width		± 0.2 (W < 10)
tolerance (mm)		± 0.3 (W > 10)
Tensile Strength (MPa)	GB/T1040.3-2006	> 10
Machine direction		
Enlongation (%)	GB/T1040.3-2006	> 100
Machine direction		
Dielectric strength (kV/mm)	GB/T 1408.1-2006	> 50
Volume resistivity (Ωm)	GB/T 1410-2006	1.00E+12
Working temperature(°C)		-200/+200
PACKING SPECIFICATIONS	FLAT PAD	STEP-PACK
Core diameter (mm)	77	77
Roll width (mm)	Tape width	100
Roll diameter (mm)	150 - 350	100 - 250
Roll width tolerance (mm)	± 0.5	± 2
Remarks	W>10 mm	No flanges
Running length (m)	250 to 600 (depending on thickness)	

Store the material in a cool, clean, and dry enviroment where the temperature should stay under 19 ℃ at all times.

Statement: The information contained in this data sheet is intended to assist yo- SHENZHEN FUTUREWAY TECHNOLOGY CO., LTD u in choice of Futureway materials. Its not intended to and does not creat any e- A: 201, Building 1, No. 86, Xiangyang Road, YanchuanCommunity, xplicit or implicit guaranties, including any graranty of marketability of the goods and for special purposes. It is also not guranteed that users can achieve the E: sales01@szfutureway.com results shown in the TDS in specific applications. They will change with different T: +86 755-23079685 applicaitons. Users should determine the suitability of Futureway materials for W: www.szfutureway.com each application.

- Yanluo, Street, Bao'an District, Shenzhen